



Mobil Super™ All-In-One Protection 0W-16

Mobil Passenger Vehicle Lube , Bangladesh

Fully Synthetic Engine Oil

Product Description

Mobil Super™ All-In-One Protection 0W-16 is brought to you by the makers of Mobil 1.

Mobil Super™ All-In-One Protection 0W-16 is a full synthetic motor oil, which contributes to the improvement of fuel saving performance while shows excellent engine protection performance.

Features and Benefits

- 1. Designed for modern and highly efficient gasoline and hybrid engines
- 2. Helps extend engine life
- 3. Outstanding wear protection for vehicles of all ages
- 4. Excellent high temperature protection
- 5. Permits extended operation at elevated temperatures without oxidative oil thickening and oil breakdown
- 6. Allows easy starting and rapid oil circulation during cold starts to protect critical engine parts
- 7. Meets or exceeds ILSAC GF-6B / API SP.

Applications

Mobil Super™ All-In-One Protection 0W-16 is recommended for petrol engines, including SUVs, MPVs, and Hybrid cars, where API SP and SAE 0W-16 viscosity grade is recommended.

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product meets or exceeds the requirements of:	
API SP	
API SP Resource Conserving	
ILSAC GF-6B	

Properties and Specifications

Property	
Grade	SAE 0W-16
Ash, Sulfated, mass%, ASTM D874	0.7

Property	
Density @ 15 C, g/ml, ASTM D1298	0.845
Flash Point, Cleveland Open Cup, °C, ASTM D92	236
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	2.3
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	7
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	36
Pour Point, °C, ASTM D97	-42
Total Base Number, mgKOH/g, ASTM D2896	7.4
Viscosity Index, ASTM D2270	163
Mini-Rotary Viscometer, Apparent Viscosity, -40 C, mPa.s, ASTM D4684	42000

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

02-2025

MJL Bangladesh PLC.

Mobil House, CWS (A) 13/A, Gulshan Avenue,

Bir Uttam Mir Shawkat Sarak, Dhaka-1212, Bangladesh.

Tel: +8802 226601427, +8802 226601428, +8802 226601429

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved